



NOTES:
 1. FOR FASTENER TORQUES, REFER TO 175R5600 CLASS A. UNLESS OTHERWISE SPECIFIED.

- ⊕ CRITICAL CHARACTERISTICS
 - ▽ KEY CHARACTERISTICS
 - INSPECTION
- MUST COMPLY TO ROHS DIRECTIVE 2011/65/EU

<small>INTERPRET DIM. & TOL. PER ASME Y14.5M-1994 ALL DIMENSIONS ARE IN MILLIMETERS TOLERANCES UNLESS OTHERWISE SPECIFIED .X±1.0 .X±0.50 <±1.0</small>			<small>THIRD ANGLE PROJECTION</small> 	<small>SCALE</small> 0.400	<small>SIZE</small> A1	<small>MATERIAL</small>
<small>— PDM CONTROLLED DRAWING — NOT VALID WITHOUT FROZEN DATE IN ID STAMP</small>					<small>FINISH</small> 	
<small>CHANGED</small> DESIGNED CHECKED	<small>SABARISH</small> Louv1	<small>MAY-16-19</small> Feb-22-19			<small>DESCRIPTION</small> 03H CIRCUIT BREAKER ONLY	
<small>CONFIDENTIAL: PROPERTY OF DANFOSS A/S NORDBORG, DENMARK. NOT TO BE HANDED OVER TO BE COPIED OR BE USED BY A THIRD PARTY. TWO OR THREE DIMENSIONAL REPRODUCTION OF CONTENTS TO BE AUTHORIZED BY DANFOSS A/S.</small>					<small>WORK NUMBER</small> 132R0192	<small>REV</small> 002 <small>SHEET</small> 3 OF 3