

The background of the entire page is a repeating pattern of the Danfoss logo. The logo consists of the word "Danfoss" in a stylized, cursive script font. This logo is repeated in a grid of red and white squares, creating a textured, woven appearance. The red squares contain the white "Danfoss" logo, while the white squares contain the red "Danfoss" logo.

The Danfoss logo, featuring the word "Danfoss" in a stylized, cursive script font.

ELIMINATOR®
Bi-flow Filter Drier

Solid core bi-flow filter drier 30 cu in.										
Refrigeration and Air Conditioning										
Type	Connection	Liquid capacity [kW] / [TR]			Drying capacity [kg] / [lbs], t = 24 °C					
		R 134A	R 404A / R 507	R 22 / R 407C / R 410A	R 134A	R 404A	R 507	R 22	R 407C	R 410A
DMB/DCB 303	3/8 in. flare	19.0 / (5.4)	15.0 / (4.3)	21.0 / (6.0)	DMB: 42.0 / (92.5)	DMB: 45.2 / (99.6)	DMB: 46.0 / (101.4)	DMB: 42.5 / (93.6)	DMB: 42.1 / (92.8)	DMB: 38.3 / (84.4)
DMB/DCB 304	1/2 in. flare	28.0 / (8.0)	20.0 / (5.7)	31.0 / (9.0)	DCB: 32.8 / (72.3)	DCB: 35.8 / (77.6)	DCB: 35.8 / (78.9)	DCB: 33.2 / (73.1)	DCB: 32.8 / (72.3)	DCB: 29.9 / (65.9)
DMB/DCB 304S	1/2 in. ODF									
DMB/DCB 305	5/8 in. flare	38.0 / (10.9)	28.0 / (8.0)	42.0 / (12.0)						
DMB/DCB 305S	5/8 in. ODF									
DMB/DCB 307S	7/8 in. ODF	43.0 / (12.3)	32.0 / (9.1)	47.0 / (13.4)						

993B9909

The Danfoss logo, featuring the word "Danfoss" in a stylized, cursive script font.

ELIMINATOR®
Bi-flow Filter Drier

MADE IN MEXICO

ELIMINATOR®

The Danfoss ELIMINATOR® Series of filter driers are the most effective all-purpose driers available today. Choose the core composition that's right for your system:

DMB – 100% molecular sieves. Designed for applications requiring the highest moisture capacity.

DCB – 80% molecular sieves with 20% activated alumina. Designed for applications requiring high moisture capacity and acid absorption capacity.