





HIGHLIGHTS

Optimize your overview

- Maintain full transparency by simulating the drive at parameter level
- Assess product and system
 performance before
 prototyping
- Software always up-to-date

Design efficiently

- Use only the simulation modules you need
- Balance speed and level
 of detail as required

Speed up and de-risk

- Speed up product development
- De-risk project execution by avoiding potential issues early
- Reduce time and cost of lab testing and on-site commissioning
- Improve safety for personnel

Digital Twin with simulation models based on actual drive code

Simulation for iC7 series: MyDrive® Virtual

Want to de-risk while speeding up **product development?**

Get started faster

With MyDrive[®] Virtual, we offer you the same product insights achievable by physically testing a real iC7 drive.

MyDrive® Virtual gives you drive models which you can use in your preferred simulation environment. MyDrive® Virtual uses the same source models as the physical drive software, to guarantee high fidelity.

Just imagine a new approach to development, which gets you to market faster. Which gives you the freedom to act on the thought: 'what if?' Imagine testing every corner of your idea with no risk of downtime, and without paying for prototypes.

By eliminating the constraints of the physical environment, you can achieve higher test coverage, and thoroughly test automation to reduce time to market.

Save cost and time

The prototypes used in new product development are very costly and time-consuming to develop, build, and maintain. With MyDrive® Virtual, you can eliminate prototypes and de-risk project execution by identifying and removing sources of failure much earlier in the development phase. You also save on laboratory time, space, and energy consumption.

With MyDrive[®] Virtual you can optimize the performance down to parameter level and thereby save money thanks to faster on-site commissioning.

1:1 Digital Twin

Use the same firmware control software and application software as the physical drive, for best-in-class simulation results, with no room for error.

Use your preferred environment

The simulation models are available in a standardized format compatible with over 150 major simulation tools, worldwide. So there's no need to invest in a new simulation environment. Just use your existing tool.



What can I use it for?

Use MyDrive® Virtual to

- De-risk project execution throughout the product lifecycle
- Assess overall performance of the whole system before using physical components
- Eliminate cost of developing prototypes and transporting them
- Reduce commissioning time on site
- Freely choose the iC7 simulation model that best meets the demands of your application.

Engineering

- Optimize system performance and energy consumption
- Evaluate diverse configurations
- Reduce the overall testing time and less needs of physical test-setups due to virtual testing
- Enable end-to-end system simulations to increase system performance

Testing

- Increase test coverage with test
 automation
- Remove time spent on building up the physical test setup
- Benchmark different drive sizes and motor types without physical hardware
- Reduce laboratory time for testing
- Reduce need for equipment
- Improve safety by testing critical scenarios in an un-stressful environment and without risk of damaging the equipment

Installation and commissioning

- Reduce commissioning time thanks to less need for physical testing
- Fine tune up-front to optimize application performance
- Run learning and testing activities on virtual applications

Maintenance and service

- Build digital twins of your products to continuously improve and monitor performance and processes
- Save process data for later use in optimization
- Improve the product with no production stop
- De-risk software updates by virtually testing first
- Test different scenarios to optimize them
- Identify sporadic failures with reduced effort
- Share configuration data and results easily

How does it work?

With the modular concept, you can choose the MyDrive® Virtual models which best reflect your requirements. In this way, you can simulate a wide variety of use cases. MyDrive[®] Virtual is built from the same source models as the physical drive software, to guarantee high accuracy. Each application model behaves identically to the drive, making it ideal for configuration and logic simulations. The iC7 drive-train model includes control firmware, enabling you to simulate actual control algorithms in the drive to evaluate power sizes and machine performance.

Appication software	Control firmware	Converter model	Machine models	Load models	Simulation models
Ø					Application model
		Ø			
\checkmark			I		Drive-train model
		S	Ø		Drive system model
Appication software	Control firmware	Converter model	Machine models	Load models	Simulation models
					Application model
		S			Converter model
					Grid-train model
				Ø	Grid system model

Your choice of environment

Use the MyDrive® Virtual models in your preferred simulation environment.

iC7 series drive-train model in Matlab Simulink simulation environment



C7_Propulsio	on_DriveTrain_Std [Co-Si	mulation, v2.0]						
MU Block Danfoss Drive	es							
Open FMU Dr	ocumentation File							
Parameters	Simulation Input	Output						
Filter by nam	e or description							
	Parameter		Value	Unit	Description			
Propul	sionApp							
Y 🗄 Valu	90							
~ 🗄 N	/1_Grid							
> 🗄	M1_2_Grid_Settings							
× 🗄	M1_3_Grid_Protection							
	P1_3_1_Invalid_Frequ	ency_Response	int32(1)		PropulsionApp.Value			
	P1_3_2_Missing_Pha	se_Response	int32(1)		PropulsionApp.Value			
	B P1_3_3_Undervoltag	e_Protection	boolean(1)		PropulsionApp.Value			
> 🔣 N	A2_Power_Conversion_D	C_Link						
> 📃 N	43_Filters_Brake_Choppe	R.						
> 🔣 N	44_Motor							
> 📃 N	M5_Application							
> 🗄 N	M6_MaintenanceService							
> 🔣 N	01_0N							
> 🗄 N	#10_Connectivity							
Motor								
Y 🗄 Valu	96							
11 N	MotorSelection		int32(2)		Motor.Value.MotorSe			
> 🖃 N	40_efa280V400p4IEn							
> 🖻 N	M1_efa315V400p4lEn							
> 15 N	A2_editron_EMPMI375T1	1002900						
DriveS	ize							
Value	90							
	DriveSizeSetup		int32(1)		DriveSize.Value.Drive			
	00_iC7_60_FX11_3N05_58	8A	int32(0)		DriveSize.Value.D0_i0			
	01_IC7_60_FX12_3N05_79	9A	int32(1)		DriveSize.Value.D1_i0			

iC7 series model in FMPy simulation environment

ile Tools Help								
🗃 O 🗿 = 🗠 🕨 32	Co-Simulatio	n V						
fter variables					۲ • ≡		Model Info	
ame	Start	Unit	Plot	Description	-	^	FMI Version	2.0
 FbProcessDataIn3 		0		FieldBus Process Data In3			FMI Type	Co-Simulation Automation and Automation and
FbProcessDataOut0				FieldBus Process Data Out0			Model Name	K7 Prosidien-Application 3td
FbProcessDataOut1				FieldBus Process Data Out1			Distorms	with O
FbProcessDataOut10				FieldBus Process Data Out10			Continuous Chates	
FbProcessDataOut2				FieldBus Process Data Out2			Continuous States	(ŵ) 😤
FbProcessDataOut3				FieldBus Process Data Out3			Event Indicators	•
FbProcessDataOut4				FieldBus Process Data Out4			Variables	500
FbProcessDataOut5				FieldBus Process Data Out5			Generation Date	2022-02-14710:54:192
FbProcessDataOut6				FieldBus Process Data Out6			Generation Tool	Simulini (R20208)
FbProcessDataOut7				FieldBus Process Data Out7			Description	Darfoss Drives
FbProcessDataOut8				FieldBus Process Data Out8				
FbProcessDataOut9				FieldBus Process Data Out9			Simulation	
FreqActual			\square	Frequency Actual			Solver	Variable-step 🖂
FreqLimitNeg		0		Sets the frequency limit for negative direction			Step Size	103
FreqLimitPos		0		Sets the frequency limit for positive direction			Relative Tolecance	10:06
FreqRef			\checkmark	Frequency Reference				
 HmiFreqRefVar 		0		Hmi Frequency Reference			Output Interval	0.001
 IOCtrIMode 		0	<u> </u>	Selects the control mode for whenever I/O is the	e act		Max. Samples	500
MCStatus			2	Motor Control Status			V Input	C:/TyPmSrc/TMPyTest/PropJppSdFmLcav
 PresetRefMode 		0		Sets the mode for the preset references.			Anely default of	at volues
 PresetRefNumber 		0	Ш	Sets the number of the preset reference to be u	sed.		Los PVI cals	
PropulsionApp							Lug me cais	
Value							Decod codding	
> M10_Connectivity							Ports	
M3_Hiters_Brake_Chopper								Philosophian Applywithturd
> III MA_MOOF								PSProcessData1=1 Contemplate/United Sectors
> III MS_Application								Provide Automatic Provide Prov
> Instruction in the service								DOCHNICOS Kartinguet
 III M3 Deven Companies DC Lin 								Prestallunter HorsenDataOlf
 mc_rower_conversion_DC_Lin RampSelectionIng.dt 	R.	0		Select the input terminal for relection between	the f			Francisco Input Histores Date Date Date Date Date Date Date Date
RunFnahle		~		Run Enable	where the second			Proglating Physical P
BunRequest				Run Remarkt				Popratia Physical Phy
time				time				Digitatist PhilycompDataOut7
 EbBrocerrDatalo0 		0	Η	FieldBur Procerr Data In0				Diginatus PhProcedualut
· I DI TOCCADONANO		× .	-	The data in the case of the time		~		Digutativ references to



iC7 series model in Dymola simulation environment



Danfoss

Features and benefits

Feature	Benefit
De-risk project execution in an early phase	Greater reliability in business model
Easily simulate different power sizes together with different motor types, filters, for early integration of individual components	Enables you to invest in the optimal solution both cost- and perfor- mance-wise.
Assess efficiency of alternative configurations in the design phase	Reduce energy consumption in the application
Minimize the extent of building test set-ups and performing physical testing by maximizing virtual testing	Reduce overall testing time and cost
Optimize parameters during the design phase	Reduce commisioning time
Capacity to run end-to-end system simulations	Improve system performance and de-risk project execution
 High level of automation during testing Test critical scenarios in a low-stress environment Eliminate risk of equipment damage 	Improve safety
 Capability to build a digital twin of your products to continuously monitor and improve performance Facilitates virtual system validation of software updates 	Efficiently maintain and improve the application over its lifetime

Supports over 150 tools globally

FMI-compliant for maximum compatibility

The iC7 models are compatible with over 150 simulation environments due to the Functional Mock-Up Interface Standard. It is used by automotive and non-automotive organizations throughout Europe, Asia and North America.

- Many simulation tools are supported:
- MATLAB & Simulink
- Ansys Twin Builder
- SIMIT
- Dymola
- DIgSILENT
- FMPy

FMI is an open standard for exchanging dynamic simulation models between different tools in a standardized format. You can select the tool best suited for each type of analysis, while keeping the same model.

MyDrive® Virtual complies with FMI.





Read more about the **fmi standard here** 🗹

AM418529686475en-000101 | © Copyright Danfoss Drives | 2023.05

Any information, including, but not limited to information on selection of product, its application or use, product design, weight, dimensions, capacity or any other technical data in product manuals, catalogues descriptions, advertisements, etc. and whether made available in writing, orally, electronically, online or via download, shall be considered informative, and is only binding if and to the extent, explicit reference is made in a quotation or order confirmation. Danfoss cannot accept any responsibility for possible errors in catalogues, prochures, videos and other material. Danfoss reserves the right to alter its products without notice. This also applies to products ordered but not delivered provided that such alterations can be made without changes to form, fit or function of the product. All trademarks in this material are property of Danfoss AVS or Danfoss group companies. Danfoss and the Danfoss logo are trademarks o Danfoss AVS.