

FC102-B1-IP66, 5.5 to 18kW
Version 1.0

ENGINEERING
TOMORROW



VLT® FC 102 HVAC Drive BIM Manufacturer Specification

Danfoss Drives, Denmark, Tel. +45 7488 2222, WEB: WWW.drives.danfoss.com, E-mail: info@danfoss.com

Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product

Manufacturer	Danfoss
Model	VLT® HVAC Drive
Description	Variable Frequency Drive for HVAC Applications
Product Type	FC-102 HVAC

Performance

Power supply and power rating	See information below
Supply Frequency	50 Hz / 60 Hz \pm 10%
Overload torque	110% for 1 minute every 10 minute
True power factor	≥ 0.9
Displacement power factor (cos ϕ)	> 0.98 near unity
THiD	$\sim 46\%$ at short circuit ratio ≥ 120
Operating temperature range	-25 ^o to 50 ^o C / -13 ^o to 122 ^o F
Power Cycle	1-2 times / min.

Output data (U,V,W)

Output voltage	0-100% of supply voltage
Output switching frequency	2-16 kHz
Ramp time	1-3600 sec.
Output frequency	0-590 Hz
Power Cycle	1-2 times / min.

Input data

Digital input (Programmable)	4 (0-24VDC, PNP/NPN)
Pulse input (Programmable)	2 (0-24VDC, PNP 0,1-110kHz - can be programmed as digital output)
Analogue input	2 (0-10V or 0/4-20mA - scaleable)

Output data

Digital output (Programmable)	2 (0-24VDC, PNP/NPN - can be programmed as input)
Relay output (Programmable)	2 (240VAC, 2A / 400VAC, 2A)
Analogue output	1 (0/4-20mA - scaleable)

Fieldbus Communication

Standard built in (RS-485)	Options (Slot -A)
FC Protocol	BACnet MSTP - MCA 109
N2 Metasys	BACnet IP - MCA125
FLN Apogee	Ethernet/IP - MCA 121
Modbus RTU	DeviceNet - MCA 104
BACnet MSTP (embedded)	LonWorks - MCA 108
	Modbus TCP - MCA 122
	PROFIBUS DP - MCA 101 or PROFINET - MCA 120

Installation

IP / Nema rating	IP66 / Type 4X
Mounting	Wall
Dimensions	Included in the Revit files
Max. motor cable length (screened)	150m / 490 Feet (H1 RFI filter & EMC ClassA1/A2 & Category C2/C3)
Max. motor cable length (unscreened)	300m / 980 Feet
Weight (kg)	23kg / 50.7lb

Approvals

RFI Filter	IEC 61800-3, Category C1 / C2 / C3
EMC emission compliance	IEC 55011 Class A1/A2/B, IEC 61000-6-3/4, IEC 61800-3 Category C1/C2/C3
Harmonic compliance	IEC/EN 61000-3-12 for short circuit ratios ≥ 120

Product Variants	
Type Code	FC-102-P5K5-T2-E66
Mains Supply (L1,L2,L3)	200-240V AC -/+ 10%
Rated kW	5.5kW / 7.5HP
Rated Continual Current (A)	24.2 Amp
Type Code	FC-102-P7K5-T2-E66
Mains Supply (L1,L2,L3)	200-240V AC -/+ 10%
Rated kW	7.5kW / 10HP
Rated Continual Current (A)	30.8 Amp
Type Code	FC-102-P11K-T2-E66
Mains Supply (L1,L2,L3)	200-240V AC -/+ 10%
Rated kW	11kW / 15HP
Rated Continual Current (A)	46.2 Amp
Type Code	FC-102-P11K-T4-E66
Mains Supply (L1,L2,L3)	380-440V AC -/+ 10%
Rated kW	11kW / 15HP
Rated Continual Current (A)	24 Amp (380-440V) / 21 Amp (441-480V)
Type Code	FC-102-P11K-T6-E66
Mains Supply (L1,L2,L3)	525-600V AC -/+ 10%
Rated kW	11kW / 15HP
Rated Continual Current (A)	18 Amp
Type Code	FC-102-P15K-T4-E66
Mains Supply (L1,L2,L3)	380-440V AC -/+ 10%
Rated kW	15kW / 20HP
Rated Continual Current (A)	32 Amp (380-440V) / 27 Amp (441-480V)