

# PLUS+1 Inputs Function Block Library 70026746v401

### **Revision History**

This file contains important supplementary and late-breaking information that may not appear in the main product documentation. We recommend that you read this file in its entirety.

# Version 4.01 (February 2019)

### What is Included

- PLUS+1 GUIDE® Function Blocks (In SDL)
- User Manual (In SDL)
- Service Tool Log Screens

### What is New

- Added existing service screens to the library structure.
- Changed font used in service screens from Tahoma to Verdana.

#### **Known issues**

None

### **Minimum Requirements**

- PLUS+1 GUIDE 10.1 or greater
- PLUS+1 Service Tool 10.1 or greater

# **Version 4.00 (June 2016)**

### What is Included

- PLUS+1 GUIDE® Function Blocks (In SDL)
- User Manual (In SDL)
- Service Tool Log Screens

#### What is New

Support for Professional Licensing.

#### **Known issues**

None

### **Minimum Requirements**

• PLUS+1 GUIDE 8.1 or greater

# **Version 3.00 (January 2016)**

### What is Included

- PLUS+1 GUIDE® Function Blocks (In SDL)
- User Manual (In SDL)
- Service Tool Log Screens

#### What is New

This library is a replacement for the input functions found SD Basic FB Library (PN: 10103408).

- Companion service tool screens that can be imported to P1D files.
- Embedded checkpoints and namespace for each function block to support service tool integration.
- IO bus for alternative connectivity to your application.
- Requires specific data types for all inputs.
- Connection errors now indicate (by page name) which input has a problem.
  - o FNR Direction
    - Direction now will not change unless feedback is zero while both Fwd Sw and Rvs Sw are false.
  - o Multi\_Dig\_In
    - Added 10% Grd Bnd hysteresis in Select mode
  - Sensor 2Pt AC
    - Added Return To Neutral Configuration
    - Added GndDetVolt signal to adjust threshold for grounded input detection
  - o Sensor 2Pt AC
    - Added Return To Neutral Configuration
    - Added GndDetVolt signal to adjust threshold for grounded input detection
  - Freq\_to\_RPM
    - Updated rounding divide function within the block.
  - Freq\_to\_Speed
    - Changed Puls/Rev limit to 1 50000.

### **Known issues**

None

# **Minimum Requirements**

• PLUS+1 GUIDE 6.1 or greater

# **Support**

### Web

https://www.danfoss.com/en/products/software/dps/plus1-software-servicessupport-and-training/plus1-support-and-services/

### **Telephone**

North America: Toll free number 1-888-50PLUS1 (1-888-507-5871)

Europe: +46 476-569 06

### E-mail

plus1helpdesk@danfoss.com

### **Terms of Use**

The Danfoss Software License Agreement completely defines the licensed use of this software.

Information in this document is provided in connection with Danfoss PLUS+1 Tool set. No license, express or implied, to any intellectual property rights is granted by this document.

Danfoss disclaims all warranties and liabilities for the use of this document and the information contained herein and assumes no responsibility for any errors, which may appear in this document, nor does Danfoss make a commitment to update the information contained herein. Danfoss reserves the right to make changes to this document at any time, without notice.

## Copyright

© 2019 Danfoss, Inc. All rights reserved.

Third party trademarks and brand names are the property of their respective owners.