



NOTES:  
 1. FOR FASTENER TORQUES, REFER TO 175R5600 CLASS A UNLESS OTHERWISE NOTED.  
 ▽ CRITICAL CHARACTERISTICS  
 ▽ KEY CHARACTERISTICS  
 ○ INSPECTION  
 MUST COMPLY TO ROHS DIRECTIVE 2011/65/EU

UNLESS OTHERWISE SPECIFIED INTERPRET DIM. & TOL. PER ASME Y14.5M-1994 ALL DIMENSIONS ARE IN MILLIMETERS X: 1.0 XXL: 0.50 ± 1.0		THIRD ANGLE PROJECTION	SCALE 0.125	SIZE A1	MATERIAL
FORM CONTROLLED DRAWING NOT VALID WITHOUT FROZEN DATE IN Q STAMP				FINISH	
CHANGED				DESCRIPTION	
DESIGNED	Danfoss 01/25/2017	MCAD, FC, E1h, IP21/IP54, Options		DRAWING NUMBER 177R0676	
CHECKED				BY D11	
CONFIDENTIAL - PROPERTY OF DANFOSS A/S NØRDBORG, DENMARK. NOT TO BE HANDED OVER TO BE COPIED OR BE USED BY A THIRD PARTY. TWO OR THREE DIMENSIONAL REPRODUCTION OF CONTENTS TO BE AUTHORIZED BY DANFOSS A/S.				SHEET P4001_E1E3 1 OF 2	

