



NOTE:
 1. BACK CHANNEL COOLING: BOTTOM IN & TOP OUT
 2. CABLE FEED: BOTTOM ENTRY & BOTTOM OUT
 3. PLINTH HEIGHT CAN BE OF 100, 200, & 400mm HEIGHT.

NOTE:
 INTERNAL CABLES CONNECTIONS ARE NOT SHOWN.

CRITICAL CHARACTERISTICS
 KEY CHARACTERISTICS
 INSPECTION
 MUST COMPLY TO ROHS DIRECTIVE 2011/65/EU

INTERPRET DIM. & TOL. PER ASME Y14.5M-1994		THIRD ANGLE PROJECTION	SCALE	SIZE	MATERIAL
ALL DIMENSIONS ARE IN MILLIMETERS			0.150	A1	
TOLERANCES UNLESS OTHERWISE SPECIFIED					
±0.10 ±0.50 ±1.0					
NOT VALID WITHOUT FROZEN DATE IN 10 STAMP					
Danfoss					
MCAID-PLV-D9H-IP54 -LHDP-FUSDIS-CON-DUDT-CM					
DESIGNED	SABARISH	WXY-21-19			
CHECKED	Louvi	Mar-03-19			
CONFIDENTIAL - PROPERTY OF DANFOSS A/S HØRSHØJ, DENMARK. NOT TO BE HANDED OVER TO BE COPIED OR BE USED BY A THIRD PARTY. TWO OR THREE DIMENSIONAL REPRODUCTION OF CONTENTS TO BE AUTHORIZED BY DANFOSS A/S.					
REVISION	132R0187	REV	002		
DATE	132R0187	SHEET	1 OF 3		



