



CONTROL COMPARTMENT DOOR IS NOT SHOWN IN THE DRAWING FOR SHOWING INTERNAL COMPONENTS IN CONTROL COMPARTMENT ONLY CONTROL COMPARTMENT UNIT IS SHOWN FOR BETTER CLARITY

NOTE:
 1. BACK CHANNEL COOLING: BOTTOM IN TOP OUT
 2. CABLE FEED: BOTTOM ENTRY & BOTTOM OUT
 3. PLINTH HEIGHT CAN BE OF 100, 200, & 400mm HEIGHT.

CRITICAL CHARACTERISTICS
 KEY CHARACTERISTICS
 INSPECTION
 MUST COMPLY TO ROHS DIRECTIVE 2011/65/EU

INTERPRET DIM. & TOL. PER ASME Y14.5M-1994		THIRD ANGLE PROJECTION	SCALE	SIZE	MATERIAL
ALL DIMENSIONS ARE IN MILLIMETERS			0.150	A1	
TOLERANCES UNLESS OTHERWISE SPECIFIED					FINISH
±0.10 ±0.50 ±1.0					DESCRIPTION
<p>— PDM CONTROLLED DRAWING — NOT VALID WITHOUT FROZEN DATE IN ID STAMP</p> <p>CHANGED: SABARISH MAY-29-19 DESIGNED: Loui FEB-12-19</p> <p>CHECKED:</p>					
<p>CONFIDENTIAL - PROPERTY OF DANFOSS A/S NORBORG, DENMARK. NOT TO BE HANDED OVER TO BE COPIED OR BE USED BY A THIRD PARTY. TWO OR THREE DIMENSIONAL REPRODUCTION OF CONTENTS TO BE AUTHORIZED BY DANFOSS A/S.</p>					
				<p>Danfoss</p> <p>MCAD-PLV-E5H-IP54 -FUSDISCON-CONTACTOR</p>	
				<p>REVISION: 002 SHEET: 1 OF 3</p>	



