



CONTROL COMPARTMENT DOOR IS NOT SHOWN IN THE DRAWING FOR SHOWING INTERNAL COMPONENTS IN CONTROL COMPARTMENT ONLY CONTROL COMPARTMENT UNIT IS SHOWN FOR BETTER CLARITY

2156.0 [84.88]  
2000.0 [78.74]

REFER NOTE 3

NOTE:  
1. BACK CHANNEL COOLING: BOTTOM IN TOP OUT  
2. CABLE FEED: BOTTOM ENTRY & BOTTOM OUT  
3. PLINTH HEIGHT CAN BE OF 100, 200, & 400mm HEIG

CRITICAL CHARACTERISTICS  
KEY CHARACTERISTICS  
INSPECTION  
MUST COMPLY TO ROHS DIRECTIVE 2011/65/EU

INTERPRET DIM. & TOL. PER ASME Y14.5M-1994 ALL DIMENSIONS ARE IN MILLIMETERS TOLERANCES UNLESS OTHERWISE SPECIFIED ±1.0    ±0.50    ±1.0		THIRD ANGLE PROJECTION	SCALE 0.150	SIZE A1	MATERIAL
— PDM CONTROLLED DRAWING — NOT VALID WITHOUT FROZEN DATE IN ID STAMP			DESCRIPTION <b>MCAD-PLV-E6H-IP54-WO-IP</b>		
CHANGED	SABARISH		MAY-29-19	REV 002	
DESIGNED	Loufi		OCT-17-18	SHEET 1 OF 3	
CHECKED					
CONFIDENTIAL - PROPERTY OF DANFOSS A/S NORBORG, DENMARK. NOT TO BE HANDED OVER TO BE COPIED OR BE USED BY A THIRD PARTY. TWO OR THREE DIMENSIONAL REPRODUCTION OF CONTENTS TO BE AUTHORIZED BY DANFOSS A/S.					



