

X8

X1 Mains 300mm²(50Nm)

X3/X4 Capacitor disconnect 120mm²(18Nm)

A/B Temperature 2,5mm²(0,8Nm)

X2 Drive 300mm²(50Nm)

513,7 ± 2,5 mm [20,2 ± 0,098 in]

PE M12

715,0 ± 2,5 mm [28,1 ± 0,098 in]

420,0 ± 2,5 mm [16,5 ± 0,098 in]

468,0 ± 2,5 mm [18,4 ± 0,098 in]

240,0 ± 1,0 mm [9,4 ± 0,039 in]

240,0 ± 1,0 mm [9,4 ± 0,039 in]

185,5 ± 4,0 mm [7,3 ± 0,157 in]

300,0 ± 1,0 mm [11,8 ± 0,039 in]

33,7 ± 2,5 mm [1,3 ± 0,098 in]

443,0 ± 2,5 mm [17,4 ± 0,098 in]


9,0 ± 1,0 mm [0,4 ± 0,039 in]

9,0 ± 1,0 mm [0,4 ± 0,039 in]

800,0 ± 2,5 mm [31,5 ± 0,098 in]

975,5 ± 4,0 mm [38,4 ± 0,157 in]

992,9 ± 4,0 mm [39,1 ± 0,157 in]



				DATE	Name	Designation	
				Drawn	24.01.2014	FR	X8 IP20 with external fan
				Reviewed	29.08.2014	MK	
				Standard	DIN 2768-1 V		
				Scale drawing	1:1		Drawing Number
				Print scale	Approx. 1:5		
R	Terminals	14.03.16	1			X8 C IP20 ef1	
R	Dimensions	04.07.14	1			1	
Status	Modifications	DATE	Name			A2	
<small>F:\16_P&D\102_Entwicklung\102_3D CAD_Baufreizezeichnungen\102_Bestteile\102_Überschwingungsfiler\Gehäuse\X8</small>							